



Red Devil



TECHNICAL DATA SHEET

PAINTER'S CAULK

DESCRIPTION

Formulated general purpose painter's caulk designed especially for ease of use and paintability. Product provides excellent adhesion to most common building substrates. Takes all types of paints and cleans up easily.

PACKAGED AS

PART #	PACKAGE	COLOR	UPC
0746	10.1 oz (300 ml) Cartridge	White	075339007464

KEY FEATURES

- Paintable
- Interior/Exterior
- Flexible
- Easy Application and Tooling
- VOC compliant

USES

Formulated for use around window & door frames, trim, baseboards, and moldings.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/L

SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking.

DIRECTIONS

1. Remove old caulking.
2. Clean and dry surface.
3. Clip off tip of nozzle/spout @ 45° angle to desired size. (Up to 3/8" bead size)
4. Load cartridge into caulking gun and apply.
5. Smooth caulk using Red Devil Caulk Smoother, Putty Knife, or Damp Cloth for neat appearance.
6. Clean up excess caulk immediately with clean, damp cloth before surface skins over.
7. Wait 2 hours before painting with latex paint, or 24 hours with oil-based paint.
8. Protect from water until cured. (72 hours), then painting is recommended.

FOR BEST RESULTS

- Apply when surface and air temperature are above freezing and below 90F.
- Joint size should not exceed 3/8". If joint depth exceeds 3/8", use backer rod. (3/8" is the Max)
- Store at temperatures above freezing and below 90F.

CLEAN UP

Mild Soap and Water.

LIMITATIONS

- Not recommended for use on fish tanks/aquariums, marine applications, mirrors, or automobiles
- Protect from rain/water exposure for 72 hours, then paint.
- Not recommended for below water line applications

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.



Red Devil



TECHNICAL DATA SHEET

PAINTER'S CAULK

PHYSICAL/PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Weight Per Gallon	Gardner Cup	14.0 +/- 1
Specific Gravity	Calculated	Approx. 1.55 to 1.80
Total Non-Volatile % Solids (Weight)	Computrac Analyzer	>80% +/- 2.5
Extrudability/Application	Semco Gun (6 oz. @ 50 psi)	12 seconds +/- 5
Consistency/Appearance	Visual Observation	Smooth, Colored Paste
pH (initial)	pH Meter	7.5 +/- 0.5
Odor	Subjective	Mild
Base Polymer	Known	Proprietary Polymer
Filler/Pigment	Known	Calcium Carbonate/TiO2
Flash Point	Closed Cup	Non-Flammable; >200F
Freeze/Thaw Stability	Test Lab 0F/77F @ 24 hrs. or ASTM C731	Pass 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Expect 1 Yr. @ 72F
Tack Free Time	Test Lab	<1 hour @ 72F
Full Cure	Test Lab	Approx. 3 Days
Storage Conditions	Test Lab	40F to 90F (5C to 32C)
Application Temperature	Test Lab	40F to 90F (5C to 32C)
Tooling	Test Lab/Field Evaluation	Excellent
% Elongation	Test Lab	200%
Service Temperature	Test Lab	-20F to 180F (-29C to 82C)
Paintability	Test Lab	24 to 72 Hours, (Paint for best results)

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING (See SDS for additional safety information)

⚠️ WARNING: Cancer Risk From Titanium Dioxide Exposure -www.P65Warnings.ca.gov

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.