



# Red Devil



## TECHNICAL DATA SHEET

# PAINTER'S PLUS

### DESCRIPTION

Painter's Plus is a premium grade caulk formulated for use on a variety of interior and exterior applications. Designed to prevent paint cracking, won't shine through paint, and is easily applied with consistent flow/without air pops. Paintable in 30 minutes, compatible with oil and water-based paints, as well as can be spray painted immediately.

### PACKAGED AS

PART #	PACKAGE	COLOR	UPC
0766	10.1 oz (300 ml) Cartridge	White	075339034040

### KEY FEATURES

- Paintable in 30 Minutes
- Interior/Exterior
- No Air Pops
- Resists Paint Cracking
- No Shine Through
- Excellent Flexibility
- Strong Adhesion
- Easy Application and Smooth Tooling
- Meets ASTM C834
- VOC compliant

### USES

Formulated for use around window & door frames, trim, baseboards, moldings, skirtings, corner joints, vents, stairs, vents, pipes.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 5 g/L

### SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking.

### DIRECTIONS

1. Remove old caulking.
2. Clean and dry surface.
3. Clip off tip of nozzle/spout @ 45° angle to desired size. (Up to 3/8" bead size)
4. Load cartridge into caulking gun and apply.
5. Smooth caulk using Red Devil Caulk Smoother, Putty Knife, or Damp Cloth for neat appearance.
6. Clean up excess caulk immediately with clean, damp cloth before surface skins over.
7. Allow 30 minutes for caulk to skin before painting or use a paint sprayer immediately.
8. When finished make sure to clean up any excess caulk, then reseal cartridge for storage and reuse.

### FOR BEST RESULTS

- Apply when surface and air temperature are between 40F and 90F.
- Store at temperatures above freezing and below 90F.

### CLEAN UP

Mild Soap and Water.

### LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics.
- Not intended for sealing building envelope.
- Not recommended for below water line applications.

### LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.



# Red Devil



## TECHNICAL DATA SHEET

### PAINTER'S PLUS

PHYSICAL/PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Weight Per Gallon	Gardner Cup	13.5
Specific Gravity	Calculated	1.60
Total Non-Volatile % Solids (Weight)	Computrac Analyzer	>85% +/- 2.5
Extrudability/Application	Semco Gun (6 oz. @ 40 psi)	802g/min
Consistency/Appearance	Visual Observation	Smooth, White Paste
pH (initial)	pH Meter	8
Odor	Subjective	Very Mild
Base Polymer	Known	Proprietary Polymer
Filler/Pigment	Known	Calcium Carbonate/TiO2
Flash Point	Closed Cup	Non-Flammable; >200F
Freeze/Thaw Stability	Test Lab 0F/77F @ 24 hrs. or ASTM C731	Pass 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Expect 1 Yr. @ 72F
Tack Free Time	Test Lab	30 Minutes
Full Cure	Test Lab	Approx. 3 Days
Storage Conditions	Test Lab	40F to 90F (5C to 32C)
Application Temperature	Test Lab	40F to 90F (5C to 32C)
Tooling	Test Lab/Field Evaluation	Excellent
% Elongation	Test Lab	113%
Service Temperature	Test Lab	-20F to 180F (-29C to 82C)
Paintability	Test Lab	Brush-Roller 30 Min/Spray Immediately

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING (See SDS for additional safety information)**

**⚠️ WARNING: Cancer Risk From Titanium Dioxide Exposure -[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

### **LIMITED WARRANTY**

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.