



Red Devil

FOAM & FILL

TECHNICAL DATA SHEET

FOAM/GUN FOAM CLEANER

DESCRIPTION

Red Devil Gun Foam Cleaner removes uncured foam from gun dispenser, tools and accessories. Formulated to clean both 1-component and 2 component uncured foam.

KEY FEATURES

- Powerful formula cleans uncured foam from foam gun dispensers.
- Cleaner designed to attach to foam applicator for internal flushing & cleaning. Also includes attached spray nozzle.
- Removes uncured foam from tools, and accessories.
- Not harmful to the ozone layer.
- Can be used in all positions.

PACKAGING

- 12 oz. Pressurized cannister with gun dispensing & spray nozzle.

CLEAN UP

Uncured Foam – Clean immediately with Red Devil Gun Foam Cleaner. Cured Foam – cannot be removed with solvents. If foam hardens on skin, use an industrial hand cleaner with pumice. Repeat if necessary. Foam that cannot be removed will wear off in time. Cured Foam on surfaces must be mechanically extracted.

ENVIROMENTAL, SAFETY & TRANSPORTATION

Do not expose to temperatures higher than 50°C/122°F. Keep away from sources of ignition. Use only in well ventilated areas. Keep out of reach of Children. SEE SDS FOR ADDITIONAL INFORMATION.

LIMITATIONS

- Cannot be used to clean cured foam.
- May damage sensitive surfaces.
- Do not expose to rain or excessive moisture for 6 hours.
- Do not apply to surfaces with excessive Moisture content.
- Flammable during dispensing.

USES

- Used to clean Foam Dispenser Guns
- Used for removal of uncured foam
- Used to clean Tools and many accessories

DIRECTIONS

- Important - Read all directions and cautions before use.
- Shake container before use and periodically during use.
- Screw cannister tightly onto gun applicator and press the trigger to flush the cleaner through the gun applicator for at least 5 seconds, or until tip is thoroughly cleaned.
- Dispense in the upside down position when attached to gun dispenser, or attached Spray Nozzle can be used.

APPLICATION PREPARATION

- Shut off all gas pilot lights, electrical igniters, burners and other sources of ignition and heat before and during use, as this product is **EXTREMELY FLAMMABLE**.
- Use protection, such as gloves and safety glasses. Avoid all contact with eyes and skin.

FOR BEST RESULTS

- Shake container before use and periodically during use.
- Dispense product with cannister in **UPSIDE-DOWN** position.
- Apply when temperatures are between 20°F and 100°F.
- Affix properly onto gun applicator for internal applicator flushing and cleaning.

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used container. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose. **CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.** Contents under pressure.

PHYSICAL/ PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Color	Visual Observation	Clear
Odor	Subjective	Solvent
Service Temperature	Test Lab	20°F to 100°F
Shelf Life	Test Lab	24 months (Stored Properly)
Storage	Test Lab	Store in cool, dry area. Store in upright position at temperatures above freezing. Avoid temps above 122°F.