



Red Devil



TECHNICAL DATA SHEET

QUICKpaint® ACRYLIC CAULK

DESCRIPTION

Specially formulated for the professional paint contractor. This fast-dry acrylic caulk, plus silicone, saves time and money by allowing fast paint over time. Just 30 minutes with latex paint, 2 hours with oil-based paint, or immediately with spray paint.

SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking. Prime bare surfaces before caulking for best results.

DIRECTIONS

1. Remove old caulking.
2. Clean and dry surface.
3. Clip off tip of nozzle/spout @ 45° angle to desired size.
4. Load cartridge into caulking gun and apply.
5. Smooth caulk using Red Devil Caulk Smoother, Putty Knife, or Damp Cloth before surface skins over.
6. Clean up excess caulk immediately with clean, damp cloth.
7. Excess cured caulk can be removed with single edge razor blade, careful not to undercut the seal.

PART #	PACKAGE	COLOR	UPC
0946	10.1 oz (300 ml) Cartridge	White	075339009949

KEY FEATURES

- Paintable in 30 Minutes with No Paint Film Cracking
- Easy to use
- Adheres to Most Construction Surfaces
- Interior/Exterior
- Paintable
- Cured Caulk is Mildew Resistant
- ASTM C834
- VOC compliant

FOR BEST RESULTS

- Apply when surface and air temperature are above freezing and below 90F.
- Joints deeper than 1/2", use a backer rod.
- Prime bare surfaces before caulking.
- Store at temperatures above freezing and below 90F.
- Do not overtool.

CLEAN UP

Mild Soap and Water.

USES

Formulated for use around window & door frames, baseboards, moldings, splashboards, eaves, and most common construction surfaces.

LIMITATIONS

- Not recommended for use on fish tanks/aquariums, marine applications, or automobiles
- Not recommended for use on mirrors
- Protect from rain/water exposure for 72 hours
- Apply only to clean, dry substrates
- Larger beads, cooler temperatures & higher humidity will slow down cure.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/L

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.



Red Devil



TECHNICAL DATA SHEET

QUICKpaint® ACRYLIC CAULK

PHYSICAL/PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Weight Per Gallon	Gardner Cup	14.0 +/- 0.50
Specific Gravity	Calculated	Approx. 1.50 to 2.0
Total Non Volatile % Solids (Weight)	Computrac Analyzer	>85% +/- 2.5
Extrudability/Application	Semco Gun (6 oz. @ 50 psi)	10 seconds +/- 3
Consistency/Appearance	Visual Observation	Creamy, Viscous Paste
pH (initial)	pH Meter	7 to 9
Odor	Subjective	Mild Acrylic
Base Polymer	Known	Styrenated Acrylic Blend
Filler/Pigment	Known	Calcium Carbonate/TiO2
Flash Point	Closed Cup	Non-Flammable; >200F
Freeze/Thaw Stability	Test Lab 0F/77F @ 24 hrs or ASTM C731	Pass 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Expect 1 Yr @ 72F
Tack Free Time	Test Lab	30 Minutes – Pass (No Stick)
Full Cure	Test Lab	72 Hours
Storage Conditions	Test Lab	40F to 90F (5C to 32C)
Application Temperature	Test Lab	40F to 90F (5C to 32C)
Tooling	Test Lab/Field Evaluation	Excellent
% Elongation	Test Lab	350%
Service Temperature	Test Lab	0F to 200F (-18C to 93C)
Coverage	Test Lab	50 – 55 Linear Feet (3/16” Bead)

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING (See SDS for additional safety information)

⚠️ WARNING: Cancer Risk From Titanium Dioxide Exposure -www.P65Warnings.ca.gov

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

