



Red Devil



TECHNICAL DATA SHEET

LIFETIME™ Ultra 230

DESCRIPTION

Premium Acrylic Latex Sealant is a high performance, multi-purpose sealant formulated to last for the lifetime of your home. This unique formulation provides maximum level durability on a variety of substrates indoors or outdoors. It offers excellent paint ability and includes HomeShield™ Antimicrobial Protection to ensure against the worst types of mold and mildew. Available in many colors.

PACKAGED AS

PART #	PACKAGE	COLOR	UPC
0770	10.1 oz (300 ml) Cartridge	White	075339011294
077010	10.1 oz (300 ml) Cartridge	Cedar	075339011287
077020	10.1 oz (300 ml) Cartridge	Almond	075339011232
077040	10.1 oz (300 ml) Cartridge	Brown	075339011256
077050	10.1 oz (300 ml) Cartridge	Gray	075339011270
077060	10.1 oz (300 ml) Cartridge	Black	075339011249
0777	10.1 oz (300 ml) Cartridge	Clear	075339011263
0705	5.5 oz (163 ml) Tube	Clear	075339016626
0775	5.5 oz (163 ml) Tube	White	075339011300

KEY FEATURES

- VOC Compliant
- Mildew-Resistant
- Maximum Durability
- Can Be Applied At Temperatures Below Freezing
- Paintable
- Superior Adhesion & Remains Flexible
- HomeShield™ Antimicrobial Protection
- ASTM 230 Class A; ASTM C920 Class 25

USES

Formulated for use on window & door frames, siding, trim, baseboards, subfloors, countertops, sinks, bathtubs, vents, concrete & metal.

CRITERIA	STATUS
CARB Compliance	Yes (Currently Exempt)
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/L

SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking. Clean metal surfaces may be primed for best results.

DIRECTIONS

1. Remove old caulking.
2. Clean and dry surface.
3. Clip off tip of nozzle/spout @ 45° angle to desired size.
4. Load cartridge into caulking gun and apply.
5. Smooth caulk using Red Devil Caulk Smoother, Red Devil Putty Knife, or Damp Cloth.
6. Wipe away excess with a damp cloth before surfaceskins over.
7. Protect from water until cured (72 hours). Full clarity reached in 1 to 2 weeks. Cool and humid conditions will extend cure time.

FOR BEST RESULTS

- Store at temperatures above freezing.
- Apply in temperatures above 40F.
- Joint width should not exceed ½". If joint depth exceeds ¼", use a backer rod.
- Prime bare surfaces before caulking.

CLEAN UP

Clean tools immediately with water. Wash skin with warmwater and soap.

LIMITATIONS

- Note recommended for automotive use.
- Not recommended for use on fish tanks/aquariums.
- Not recommended for use on mirrors.
- Not recommended for below grade applications.
- Not recommended for below waterline applications.
- Protect from water until cured (72 hours) – Cooler temperatures & higher humidity will extend cure time.



Red Devil



TECHNICAL DATA SHEET

LIFETIME™ Ultra 230

PHYSICAL/PERFORMANCE PROPERTY	TEST METHOD	TYPICAL RESULT
Weight Per Gallon	Gardner Cup	12 +/- 2.0
Specific Gravity	Calculated	Approx. 1.40 to 1.50
Total Non-Volatile % Solids (Weight)	Computrac Analyzer	> 80% +/- 2.5
Viscosity	Semco Gun @ 50 psi	Approx. 8 sec. +/- 2
Consistency/Appearance	Visual Observation	Smooth, Colored Paste
Flash Point	Closed Cup	>200F – Non-Flame/Waterborne
Odor	Subjective	Mild
Base Polymer	Known	Acrylic Emulsion Blend
Filler/Pigment	Known	Calcium Carbonate, TiO2
pH (initial)	pH Meter	7 to 9
Freeze/Thaw Stability	Test Lab 0F/77F @ 24 hrs. or ASTM C731	Pass 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Expect 1 Yr. @ 72F
Tack Free Time	Test Lab	< 1 hr. @ 72F
Full Cure	Test Lab	72 Hours – cool & humid will extend
Storage Conditions	Test Lab	Original Container: 40F to 90F
Application Temperature	Test Lab	40F to 90F (4C to 32C)
Painting	Test Lab	Latex: 4-6 hrs., Oil-based: 24 hrs.
% Elongation	Test Lab	700% Minimum
Service Temperature	Test Lab	-20F to 180F (-29C to 82C)
Clean Up	Test Lab	Water – Before Cure



- : Warning
- : Causes serious eye irritation.
- : Causes skin irritation.
- : May cause respiratory irritation.

(SEE SDS FOR ADDITIONAL INFORMATION)

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING (See SDS for additional safety information)

⚠️ WARNING: Cancer Risk From Titanium Dioxide & Carbon Black Exposure
-www.P65Warnings.ca.gov

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.