

### **0583 Caulk Remover – Liquid:**

- **What is the base chemistry of 0583?** Proprietary blend.
- **Is Caulk Remover VOC Compliant?** Yes. Product suitable for sale in California & OTC areas.
- **Are any Prop 65 Ingredients added during the formulation of this product?** No.
- **What is the appearance & odor of 0583?** Product is a cream-like fluid, off-white in color, with a mild ester odor.
- **Is 0583 considered flammable?** No. Product exhibits a flash point of > 225F.
- **Is 0583 suitable for interior or exterior use?** Yes.
- **Does the product work on various types of caulk?** Yes.
- **How does the product work?** It softens caulk for easy removal.
- **Is 0583 decidedly acidic or alkaline?** No – product exhibits basically a neutral pH @ approximately 7.0 – similar to water.
- **How should product be used?** Apply product directly to surface of caulk to be removed.
- **Are there “general” directions for individuals unfamiliar with liquid caulk remover?** Yes. Caulk Remover should be stored above freezing. Apply product when material, air temperature & surface are 40F to 90F, applying approximately a 1/8<sup>th</sup> inch coat to cured caulk to be removed & allow to soften caulk (typically a minimum of 2 hrs) – some caulks such as Acrylics may require up to 7 hrs to soften. When caulk has softened considerably, use a putty knife to remove as much as possible. Apply a 2<sup>nd</sup> application & repeat as required – especially for painted caulk. Carefully remove remaining film with a razor blade, taking care not to damage surface. Clean & dry the substrate prior to application of new/replacement caulk. Caulk Remover should remain sealed & stored in a cool dry location when not in use.
- **What is the consistency of Caulk Remover as supplied?** Cream-like fluid.
- **What is the color of Caulk Remover as supplied?** White to off-white.
- **What clean up procedures are recommended?** Soap & water.
- **Is Caulk Remover safe for all surfaces?** Not determined. To avoid possible damage, test in a small inconspicuous spot (some Fiberglass, other Plastic or refinished surfaces may be affected)
- **Can Caulk Remover damage paint & wallpaper?** Possibly – Caulk Remover should be wiped-off these surfaces immediately to avoid possible damage.
- **What is the standard packaging for Red Devil Caulk Remover?** 8 oz HDPE Squeeze Bottle.
- **Is Caulk Remover Freeze-Thaw stable?** No. Protect from freezing.
- **Are there other surfaces to which Caulk Remover should not be applied?** Yes. Do not use on low-end ABS Plastic Tubs & Showers or on old-fashioned plastic wall tiles.
- **Is 0583 DOT Regulated?** No.
- **Are gloves recommended?** Yes. See MSDS.
- **Where can additional information be found on 0583 Caulk Remover?** See MSDS & TDS on this website ([www.reddevil.com](http://www.reddevil.com)).

