

# Safety Data Sheet

Issue Date 16-Jul-2013	Revision Date: 01-Oct-2017	Version 1
	1. IDENTIFICATION	
<u>Product Identifier</u> Product Name	Wall & Counter Caulk Strip – Butyl Based - White	
Other means of identification SDS #	RD-0005	
Product Code	0155	
Recommended use of the chemical and restrictions on use         Recommended Use       For use between walls & countertops.         Details of the supplier of the safety data sheet         Supplier Address		
Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com		
Emergency Telephone Number Company Phone Number Emergency Telephone (24 hr)	918-825-5744 Fax: 918-825-5761 INFOTRAC 1-352-323-3500 (International)	
	1-800-535-5053 (North America)	
2. HAZARDS IDENTIFICATION		

# **Classification**

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Appearance White; Self-adhesive strip

Physical State Preformed caulk strip

Odor Slight solvent

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
Calcium Carbonate	1317-65-3	>70
Proprietary Butyl Mastic	MIXTURE	<20
Non-Haz Ingredients*	Proprietary	>10

\* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Crystalline Silica) Inhalation of particulates unlikely due to product's physical state. Crystalline Silica (as Quartz) present @ low levels in Calcium Carbonate filler.

# **4. FIRST-AID MEASURES**

#### **First Aid Measures**

General Advice	Provide this SDS to medical personnel for treatment. Get medical attention for any significant overexposure.
Eye Contact	Flush w/ water for @ least 15 minutes. If irritation persists, get medical attention.
Skin Contact	Wash area thoroughly w/ soap & water. If irritation develops or persists, get medical attention.
Inhalation	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Ingestion	Do not induce vomiting unless advised by a physician. Call nearest poison control center or physician immediately.

# Most important symptoms and effects

Symptoms	Adhesive backing on strip may cause skin irritation w/ prolonged or repeated contact. May
	cause eye irritation. High vapor concentrations may irritate respiratory tract.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician	Aggravated Medical Conditions: Pre-existing eye, skin & respiratory disorders may be
	aggravated by exposure.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire	Carbon Dioxide, Dry Chemical, Foam, Water Fog.
Large Fire	Carbon Dioxide, Dry Chemical, Foam, Water Fog.

Unsuitable Extinguishing Media Not determined.

<u>Specific Hazards Arising from the Chemical</u> Butyl adhesive on back of strip is flammable. Caulk strip is combustible. & Explosion Conditions: Product not expected to ignite in normal conditions of use.

# Hazardous Combustion Products Carbon oxides.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions	Wear gloves, goggles, appropriate respirator & protective clothing, if large amount of rolls involved.		
Methods and material for containm	ent and cleaning up		
Methods for Containment	Prevent further leakage or spillage if safe to do so.		
Methods for Clean-Up	Caulk strips can normally be picked up.		
7. HANDLING AND STORAGE			
Precautions for safe handling			
Advice on Safe Handling	Handle in accordance with good industrial hygiene and safety practice. Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes & skin. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Store caulk strip rolls away from excessive heat. Do not store @ temperatures above 120F.		
Incompatible Materials	Strong oxidizing agents.		

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate	-	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> total dust
1317-65-3		TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total	
		dust	
		(vacated) TWA: 5 mg/m <sup>3</sup>	
		respirable fraction	

#### Appropriate engineering controls

**Engineering Controls** General ventilation sufficient.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Avoid contact with eyes.

Skin and Body Protection Avoid repeated or prolonged skin contact. Hand protection: Use suitable impervious rubber or vinyl gloves & protective apparel to reduce exposure. Respiratory ProtectionNot required under normal conditions of use. Wear appropriate, properly fitted<br/>NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant<br/>level(s) are expected to exceed exposure limits indicated on SDS. Follow manufacturer's<br/>directions for respirator use.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Use professional judgment in selection, care & use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State Appearance Color	Preformed caulk strip White; Self-adhesive strip White	Odor Odor Threshold	Slight solvent Not determined
Property pH Melting Point/Freezing Point Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit Vapor Pressure Vapor Density Specific Gravity	ValuesNot applicableNot availableNot availableNot determinedNot determinedNot determinedNot determinedNot determinedNot determinedNot determinedNot determinedNot availableNot availableNot availableNot availableNot available	Odor Threshold <u>Remarks • Method</u>	Not determined
Water Solubility Solubility in other solvents	Not available Not determined		
Partition Coefficient Autoignition Temperature Decomposition Temperature Kinematic Viscosity Dynamic Viscosity Explosive Properties Oxidizing Properties VOC Content	Not determined Not determined Not determined Not determined Not determined Not determined Not determined Not determined 12-13% / wt		

# **10. STABILITY AND REACTIVITY**

# Reactivity

Not reactive under normal conditions.

#### **Chemical Stability**

Stable under recommended storage conditions.

# Possibility of Hazardous Reactions

None under normal processing.

#### <u>Conditions to Avoid</u> Excessive temperature.

Incompatible Materials

Strong oxidizing agents.

# Hazardous Decomposition Products

None known based on information supplied.

# **11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Product Information	
Eye Contact	May cause temporary irritation on eye contact.
Skin Contact	Prolonged or repeated contact with adhesive backing may cause skin irritation.
Inhalation	Vapor may irritate respiratory tract.
Ingestion	Do not taste or swallow.
Component Information	
Information on physical, chemical	and toxicological effects
Symptoms	Please see section 4 of this SDS for symptoms.
Delayed and immediate effects as	well as chronic effects from short and long-term exposure
Carcinogenicity	Inhalation of crystalline silica as quartz (small percentage present in calcium carbonate filler) can cause cancer based on animal data. IARC concludes sufficient evidence in humans (Group 1). Prolonged & repeated overexposure to free crystalline silica dust above TLV level may cause scarring of the lungs, coughing & shortness of breath. Note: Inhalation of crystalline silica from normal use is unlikely, due to products physical state.

## Numerical measures of toxicity

Not determined

# **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# Persistence/Degradability

Not determined

Bioaccumulation Not determined

Mobility Not determined

# Other Adverse Effects

Not determined

# 13. DISPOSAL CONSIDERATIONS

# Waste Treatment Methods

**Disposal of Wastes** 

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

# **14. TRANSPORT INFORMATION**

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
DOT	Not regulated
IATA	Not regulated
IMDG_	Not regulated

# **15. REGULATORY INFORMATION**

# International Inventories

Not determined

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

#### US Federal Regulations

# <u>SARA 313</u>

Not determined

#### US State Regulations

#### **California Proposition 65**

Warning: Contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Silica, crystalline @ low levels in Calcium Carbonate Filler.

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate	Х	Х	Х
1317-65-3			

# **16. OTHER INFORMATION**

<u>NFPA</u> HMIS	Health Hazards Not determined Health Hazards 1	Flammability Not determined Flammability 1	<b>Instability</b> Not determined <b>Physical Hazards</b> 0	Special Hazards Not determined Personal Protection Not determined
Issue Date Revision Date: Revision Note	16-Jul-2013 01-Oct-2017 New format			

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# End of Safety Data Sheet