

0522/528 Instant Woodfiller – Pre-mixed Paste:

- What is the base chemistry of this product? Solvent based, fortified with other ingredients.
- Does this pre-mixed woodfiller formula meet any recognized specifications? Yes. Product complies with Federal Specification TT-F-340B.
- Does this product contain real wood fibers? Yes.
- **Is product stainable?** Yes, following full cure & sanding.
- Will fully cured product hold screws & nails without splitting? Yes.
- Is this product water-resistant after full cure? Yes.
- What is the cure time for a small repair? This rapid-cure formula is generally tack free in 10 to 20 minutes & ready for sanding within 1 to 2 hours, depending on atmospheric conditions, patch size & porosity of substrate. Full cure is typically 24 hrs in normal conditions.
- Is this product suitable for interior or exterior applications? Yes. Note label & MSDS; product is solvent based & flammable.
- What is the primary application for this product? Product repairs all types of wood.
- Will product adhere to any substrates other than wood? Yes. Product will generally provide adequate adhesion to stone, some metals & hardboard, provided substrate has been properly prepared (clean, free of contaminants, etc)
- What are some key limitations of this product? Product is solvent based & extremely flammable. Product is a skin & eye irritant & exhibits harmful vapors. (Consult MSDS). Larger holes may require two or more applications.
- What color is this woodfiller product as supplied? Natural Beige.
- Is formula VOC Compliant? No.
- **Does formula contain any Prop 65 Ingredients?** Yes. Formula contains < 10% Toluene known to the state of California to cause cancer or reproductive harm.
- **Is product Flammable?** Yes extremely flammable (see MSDS for additional information).
- Does formula contain any SARA Section 313 listed ingredients? Yes, product contains Acetone.
- Where can additional information be found on this product? See MSDS & TDS on this website (www.reddevil.com).