0838 House & Home Restore Kitchen & Bath Caulk:

- What is the base chemistry for this product? Complex acrylic emulsion, fortified with silicone & additional mildew resistance additive.
- Is 0838 a VOC Compliant product? Yes. Product is suitable for sale in California, OTC & other regulated areas.
- Does 0838 contain any Prop 65 Ingredients? Yes (see MSDS)
- Is 0838 a water clean up product? Yes.
- Does 0838 contain an adhesion promoter? Yes.
- What is the color of 0838 as supplied? White.
- **Does 0838 exhibit any odor during application & curing?** Yes, a mild acrylic latex odor that is not present @ full cure.
- How much shrinkage should be expected with 0838? < 30%.
- What is the recommended temperature range for application of 0838? 40F to 90F.
- What is the approximate cure time for 0838? Approximately 72 hrs for a 3/16 inch bead. Conditions of cooler temperatures &/or higher humidity will extend cure time.
- Can 0838 be painted? Yes.
- Is 0838 Freeze-Thaw Stable? Yes, formula will typically withstand 5 cycles of F/T @ 0 degrees F & 72 degrees F.
- Does 0838 remain flexible after cure? Yes.
- How is the crack resistance & water resistance of 0838 after full cure? Excellent when used according to directions.
- Where can additional information be found regarding 0838? See MSDS & TDS on this website (<u>www.reddevil.com</u>).