



# Safety Data Sheet

Issue Date 29-Aug-2013

Revision Date: 01-Oct-2017

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Zip-A-Way Removable Sealant – Solvent Based - Clear

### Other means of identification

**SDS #** RD-0042

**UN/ID No** UN1993  
**Product Code** 0606 Series

### Recommended use of the chemical and restrictions on use

**Recommended Use** Specially formulated weather stripping caulk to provide a tight, temporary seal that can easily be peeled away when no longer needed.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Red Devil, Inc.  
4175 Webb Street  
Pryor, Oklahoma 74361  
www.reddevil.com

### Emergency Telephone Number

**Company Phone Number** 918-825-5744  
Fax: 918-825-5761  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Clear viscous

**Physical State** Viscous paste

**Odor** Solvent

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

### Signal Word

**Danger**

**Hazard Statements**

Causes skin irritation  
Causes serious eye irritation  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Get medical attention  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do not induce vomiting  
IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Harmful to aquatic life with long lasting effects  
Harmful to aquatic life

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Toluene	108-88-3	<25
Polyalicyclic resin	MIXTURE	<20
Mineral Oil	8042-47-5	<20
Light aliphatic solvent naphtha	64742-48-9	<20
Non-hazardous Ingredients*	Proprietary	<19

\*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### 4. FIRST-AID MEASURES

#### First Aid Measures

<b>General Advice</b>	Provide this SDS to medical personnel for treatment. Get medical attention for any overexposure.
<b>Eye Contact</b>	Immediately flush w/ large quantities of water for @ least 15 minutes, until irritation subsides. Get medical attention.
<b>Skin Contact</b>	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing difficult, give oxygen & contact physician immediately. Only trained individuals should give artificial or administer oxygen.
<b>Ingestion</b>	Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention.

#### Most important symptoms and effects

<b>Symptoms</b>	<p>Inhalation: Vapor harmful if inhaled. Vapor may irritate nose &amp; upper respiratory tract. Inhaled vapor may affect brain or nervous system resulting in dizziness, headache or nausea. Prolonged vapor inhalation may result in severe physical injury.</p> <p>Eyes: Causes eye irritation.</p> <p>Ingestion: Material may be harmful or fatal if swallowed. Aspiration of material into lungs due to vomiting can cause chemical pneumonitis, which can be fatal. If ingested, product may cause vomiting, diarrhea &amp; depressed respiration.</p> <p>Skin: May irritate skin. Prolonged or repeated contact can result in defatting &amp; drying of the skin which can result in skin irritation &amp; dermatitis (skin rash). Can be absorbed through skin.</p>
-----------------	--

#### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Provide general supportive measures and treat symptomatically. Aggravated Medical Conditions: Pre-existing eye, skin & respiratory disorders may be aggravated by exposure.
---------------------------	---

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Fire & Explosion Conditions: Flammable. Material will readily ignite @ RT. Vapors may form explosive mixture w/ air. Vapors can travel long distances to a source of ignition & flash back. Eliminate ignition sources: heat, electrical equipment, sparks, pilot lights, stoves & flames. Do not smoke or put in contact w/ oxidizing or caustic materials. Containers may explode if exposed to heat.

**Hazardous Combustion Products** Smoke, fumes. Carbon monoxide & carbon dioxide can form.

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
<b>Other Information</b>	Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots & eye protection). Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.
<b>For Emergency Responders</b>	Restrict access to spill area.
<b>Environmental Precautions</b>	Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed. See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.
<b>Methods for Clean-Up</b>	Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Use only with adequate ventilation. Do not breathe vapors. Wear eye/face protection. Wash thoroughly with soap and water after handling. Avoid contact with skin, eyes or clothing. While handling product keep out of reach of children and pets. Do not eat or drink while handling this material. See section 6 of this SDS for clean up instructions. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from incompatible materials. Protect from direct sunlight.

#### **Incompatible Materials**

Strong oxidizing agents, Caustics.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>

### Appropriate engineering controls

#### **Engineering Controls**

Provide sufficient general &/or local exhaust ventilation to maintain exposure below recommended exposure limits. Vapors are heavier than air & may spread along floors. Provide fresh air entry during application & curing. Eye wash fountain should be located in immediate work area.

### Individual protection measures, such as personal protective equipment

#### **Eye/Face Protection**

Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations & standards.

#### **Skin and Body Protection**

Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations & standards.

#### **Respiratory Protection**

If watering of eyes experienced, headache or dizziness or if used in workplace & air monitoring indicates vapor levels above exposure limits, use NIOSH approved respiratory protection in accordance w/ Federal, State & Local requirements. Consult safety equipment supplier & OSHA Regulation 29 CFR 1910.134 for respirator requirements.

#### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Remove & wash contaminated clothing before reuse. Wash hands before breaks & @ end of workday.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Viscous paste	<b>Odor</b>	Solvent
<b>Appearance</b>	Clear viscous	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Clear		

Property	Note: The information below is not intended for use in preparing product specifications	Remarks • Method
pH	Not applicable	
Melting Point/Freezing Point	Not established	
Boiling Point/Boiling Range	> 87.77 °C / >190 °F	
Flash Point	< 37.77 °C / < 100 °F	CC (closed cup)
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	~8.0%	
Lower Flammability Limit	~1.0%	
Vapor Pressure	Not available	
Vapor Density	Heavier than air (>1)	
Specific Gravity	~0.75-1.25 (calculated)	
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Not available	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content (%)	37%	
VOC Content	<400 g/L	
Density	~ 1.20 g/cm <sup>3</sup> @ 68°F (20 C)	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
---------------------------------	--

### Conditions to Avoid

Incompatible Materials. Heat, sparks & open flame.

### Incompatible Materials

Strong oxidizing agents, Caustics.

### Hazardous Decomposition Products

Nitrogen oxides (NO<sub>x</sub>). Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Eye Contact</b>	Causes serious eye irritation. Eye contact may result in tearing, redness & pain.
<b>Skin Contact</b>	Causes skin irritation. Repeated skin contact may cause dermatitis.
<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Ingestion</b>	May be fatal if swallowed and enters airways. May be harmful if swallowed.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 636 mg/kg ( Rat )	= 8390 mg/kg ( Rabbit ) = 12124 mg/kg ( Rat )	= 12.5 mg/L ( Rat ) 4 h > 26700 ppm ( Rat ) 1 h
Light aliphatic solvent naphtha 64742-48-9	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	-
Mineral Oil 8042-47-5	> 5000 mg/kg ( Rat )	-	-

### Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** Not known to be human skin or respiratory sensitizers.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		

*IARC (International Agency for Research on Cancer)*

*Group 3 IARC components are "not classifiable as human carcinogens"*

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Chronic toxicity** Reports have associated permanent brain & nervous system damage w/ prolonged & repeated occupational overexposure to solvents. Symptoms include: loss of memory, loss of intellectual ability & loss of coordination. Overexposure or misuse of toluene can cause liver, kidney & brain damage as well as cardiac abnormalities & reproductive toxicity & is known to the State of California to cause cancer.

**Target organ effects** Acute: Eyes & Skin. Chronic: Skin.

**Aspiration hazard** May be fatal if swallowed and enters airways.

### Numerical measures of toxicity

Not determined

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

### Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Light aliphatic solvent naphtha 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		2.6: 96 h Chaetogammarus marinus mg/L LC50
Mineral Oil 8042-47-5		10000: 96 h Lepomis macrochirus mg/L LC50		

### Persistence/Degradability

Not tested for persistence & biodegradability

### Bioaccumulation

Not tested for bio-accumulation potential

### Mobility

Chemical Name	Partition Coefficient
Toluene 108-88-3	2.65
Mineral Oil 8042-47-5	6

### Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

## 13. DISPOSAL CONSIDERATIONS

### Waste Treatment Methods

#### **Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### **Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Not Applicable

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable

**14. TRANSPORT INFORMATION****Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

UN/ID No UN1993  
 Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Petroleum Distillate)  
 Hazard Class 3  
 Packing Group III

**IATA**

UN/ID No UN1993  
 Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Petroleum Distillate)  
 Hazard Class 3  
 Packing Group III

**IMDG**

UN/ID No UN1993  
 Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Petroleum Distillate)  
 Hazard Class 3  
 Packing Group III  
 Marine Pollutant This material may meet the definition of a marine pollutant

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Listed
<b>DSL</b>	Listed
<b>NDSL</b>	Listed

#### **Legend:**

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

*EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

*ENCS - Japan Existing and New Chemical Substances*

*IECSC - China Inventory of Existing Chemical Substances*

*KECL - Korean Existing and Evaluated Chemical Substances*

*PICCS - Philippines Inventory of Chemicals and Chemical Substances*

### US Federal Regulations

#### CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

#### SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	<25	1.0

#### CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3 ( <25 )	1000 lb	X	X	X

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental Female Reproductive

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Toluene 108-88-3	X	X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	2	3	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	2	3	0	X

**Issue Date** 29-Aug-2013  
**Revision Date:** 01-Oct-2017  
**Revision Note** New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**