

SAFETY DATA SHEET

Issue Date 31-Jan-2013

Revision Date 01-Oct-2017

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Product Name	Lifetime PRO Sealant
Other Means of Identification SDS #	RD-0097
Product Code	0856PR Series
Recommended Use of the Chemical	and Restrictions on Use
Recommended Use	Aqueous White Sealant w/ Silicone (White & Colors).
Details of the Supplier of the Safety Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com	Data Sheet
Emergency Telephone Number Company Phone Number Emergency Telephone	918-825-5744 Fax: 918-825-5761 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White and colored paste

Physical State Smooth paste

Odor Mild acrylic

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Calcium Carbonate	1317-65-3	<55
Acrylic Emulsion	MIXTURE	<30
Benzoate Ester	Proprietary	<8
Titanium dioxide	13463-67-7	<2
Non-hazardous Ingredients*	Proprietary	<5
Carbon Black	1333-86-4	0-0.25
Ammonium Hydroxide	7664-41-7	<0.25
Petroleum Hydrocarbon	64742-48-9	<0.75

* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state. (Carbon Black) May be present in colors other than White.

4. FIRST AID MEASURES

First Aid Measures		
General Advice	Provide this SDS to medical personnel for treatment.	
Inhalation	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.	
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice.	
Ingestion	Do not induce vomiting, unless directed by medical personnel. Get immediate medical attention. If vomiting occurs, keep head low so that stomach content does not get into the lungs.	
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If irritation persists, seek medical attention.	
Most Important Symptoms and Effects, both Acute and Delayed		
Symptoms	Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.	
Indication of any Immediate Medical Attention and Special Treatment Needed		
Note to Physicians	Provide general supportive measures and treat symptomatically. May aggravate pre-existing skin disorders.	
5 FIRE-FIGHTING MEASURES		

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u> Carbon dioxide (CO2). Dry chemical. Water spray (fog). Foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

Hazardous Combustion	Carbon, titanium & iron oxides, depending upon formulation.
Products	

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Restrict access to spill area. Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater.	
For Emergency Responders		
Environmental Precautions		
Methods and Material for Containment and Cleaning Up		
Methods for Containment	Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.	
Methods for Cleaning Up	Sweep up absorbed material and shovel into suitable containers for disposal. Wash area	

7. HANDLING AND STORAGE

with soap and water. For waste disposal, see section 13 of the SDS.

Precautions for Safe Handling

Advice on Safe Handling	Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to
	ensure fresh air cross-ventilation during application and curing. Wash thoroughly with soap
	and water after handling. Avoid contact with skin, eyes or clothing. While handling product
	keep out of reach of childrens and pets.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions	Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120 ° F. To maximize shelf life, store @ temperatures below 26C (80F).
Incompatible Materials	Oxidizers. Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

RD-0097 - Lifetime PRO Sealant

Revision Date 01-Oct-2017

Carbon Black	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	-	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
		. , _	TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH
Ammonium Hydroxide	STEL: 35 ppm	TWA: 50 ppm	IDLH: 300 ppm
7664-41-7	TWA: 25 ppm	TWA: 35 mg/m ³	TWA: 25 ppm
		(vacated) STEL: 35 ppm	TWA: 18 mg/m ³
		(vacated) STEL: 27 mg/m ³	STEL: 35 ppm
			STEL: 27 mg/m ³

Appropriate Engineering Controls

Engineering Controls	Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.	
Individual Protection Measures, s	uch as Personal Protective Equipment	
Eye/Face Protection	Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations & standards.	
Skin and Body Protection	Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations & standards.	
	Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment)or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations & standards.	
Respiratory Protection	If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below 19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.	

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Appearance Color	Smooth paste White and colored paste Multi-color	Odor Odor Threshold	Mild acrylic Not determined
Property pH Melting Point/Freezing Point Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit Vapor Pressure Vapor Density Specific Gravity Water Solubility	Values 7.0-10.0 < 0 °C / <32 °F Not Established > 93.33 °C / > 200 °F Not determined Not determined Unknown Unknown Not established Heavier than air ~1.55-1.65 Soluble in water	Remarks • Method @ 25 °C (77 °F)	
Solubility in Other Solvents Partition Coefficient Autoignition Temperature Decomposition Temperature	Not determined Not determined Unknown Not determined		

Kinematic Viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined
VOC Content (%)	<1.5%

10. STABILITY AND REACTIVITY

Reactivity

Cures upon contact with air.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Oxidizers. Strong acids.

Hazardous Decomposition Products

Thermal decomposition can generate irritating dust, fumes and toxic gases (carbon, titanium, and iron oxides, depending upon formulation).

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information	
Inhalation	Mildly irritating to respiratory tract.
Eye Contact	May cause temporary irritation on eye contact.
Skin Contact	Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.
Ingestion	May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Ammonium Hydroxide 7664-41-7	= 350 mg/kg (Rat)	-	= 5.1 mg/L (Rat) 1 h = 2000 ppm (Rat) 4 h
Petroleum Hydrocarbon 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-

Information on Physical, Chemical and Toxicological Effects

Symptoms

Please see section 4 of this SDS for symptoms.

Carcinogenicity

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Sensitization	Not known to be human skin or respiratory sensitizers	s.
Sensitization	Not known to be numan skin of respiratory sensitize	ers

The table below indicates whether each agency has listed any ingredient as a carcinogen. Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard. Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		Х
Carbon Black 1333-86-4	A3	Group 2B		Х

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION. Product not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50
Ammonium Hydroxide 7664-41-7		0.44: 96 h Cyprinus carpio mg/L LC50 0.26 - 4.6: 96 h Lepomis macrochirus mg/L LC50 1.17: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.73 - 2.35: 96 h Pimephales promelas mg/L LC50 5.9: 96 h Pimephales promelas mg/L LC50 static 1.5: 96 h Poecilia reticulata mg/L LC50 1.19: 96 h Poecilia reticulata mg/L LC50 static		25.4: 48 h Daphnia magna mg/L LC50
Petroleum Hydrocarbon 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		2.6: 96 h Chaetogammarus marinus mg/L LC50

Persistence and Degradability

Not tested for persistence & biodegradability

Bioaccumulation

Not tested for bio-accumulation potential

<u>Mobility</u>

Not tested for mobility in soil

Chemical Name	Partition Coefficient	
Ammonium Hydroxide	-1.14	
7664-41-7		

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

<u>Ozone</u>

Not expected to produce any ozone depletion

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods	
Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.
US EPA Waste Number	Not applicable.

14. TRANSPORT INFORMATION		
Note	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.	
DOT	Not regulated	
IATA	Not regulated	
IMDG	Not regulated	

15. REGULATORY INFORMATION

International Inventories

Not Determined

TSCA	Listed
DSL	Listed
NDSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 313 Not determined

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ammonium Hydroxide - 7664-41-7	7664-41-7	<0.25	1.0
Acute health hazard	Yes		
Chronic Health Hazard	No		
Fire hazard	No		

Sudden release of pressure hazard Reactive Hazard

No
No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide 7664-41-7	100 lb			Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium Hydroxide	100 lb	100 lb	RQ 100 lb final RQ
7664-41-7			RQ 45.4 kg final RQ

US State Regulations

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Carbon Black - 1333-86-4	Carcinogen	

U.S. State Right-to-Know Regulations Not Determined

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	Х	X	х
Titanium dioxide 13463-67-7	Х	X	Х
Carbon Black 1333-86-4	Х	X	Х
Ammonium Hydroxide 7664-41-7	Х	X	Х

16. OTHER INFORMATION

NFPA HMIS	Health Hazards 1 Health Hazards 1	Flammability 1 Flammability 1	Instability 0 Physical Hazards 0	Special Hazards Not determined Personal Protection Not determined
Issue Date Revision Date Revision Note	31-Jan-2013 01-Oct-2017 New format			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet